



SmartBright LED Downlight

DN029B G2 LED10/CCT PSR-E D120 GM

SmartBright LED Downlight, 9 W, 1000 lm, 3000 K, Beam angle 100°, White

When switching from conventional CFL to LED lighting, most customers want a green solution with an attractive total cost of ownership. SmartBright LED Downlight is characterized by low cost and high efficiency, providing the end-user with the perfect green light fixture.

Product data

General Information		Optic type	
Light source replaceable	No	Beam angle	100°
Number of gear units	1 unit	Luminaire light beam spread	100°
Driver included	Yes	Operating and Electrical	
Lighting Technology	LED	Input Voltage	220 to 240 V
Warranty period	3 years	Line Frequency	50 or 60 Hz
Light Technical		Input Frequency	50 or 60 Hz
Luminous Flux	1,000 lm	Inrush current	1.26 A
Correlated Color Temperature (Nom)	3000 K	Inrush time	0.038 ms
Luminous Efficacy (rated) (Nom)	111 lm/W	Power Consumption	9 W
Color rendering index (CRI)	80	Power Factor (Fraction)	0.8
Light source color	3000/4000/6500	Connection	Flying leads/wires
		Cable	Cable without plug
		Number of products on MCB of 16 A type B	284

SmartBright LED Downlight

Suitable for random switching	Not applicable
Protection class IEC	Safety class II

Controls and Dimming

Dimmable	Yes
Constant light output	No
Maximum dim level	10% (depends on dimmer, ELV)


Mechanical and Housing

Housing Material	Metal-Plastic
Reflector material	-
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Stainless steel
Housing Color	White
Optical cover finish	Frosted
Overall height	59 mm
Overall diameter	140 mm
Ingress protection code	IP40/54 [Finger-protected; dust accumulation-protected, splash-proof]
Mech. impact protection code	IK03 [0.3 J]
Net Weight (Piece)	0.315 kg

Approval and Application

Glow-wire test	Temperature 750 °C, duration 5 s
Flammability mark	For mounting on normally flammable surfaces
EU RoHS compliant	Yes
Ambient temperature range	-20 to +40 °C

Dimensional drawing



Initial Performance (IEC Compliant)

Luminous flux tolerance	3000K: ±10%; 4000K: -10% / +20%; 6500K: -10% / +20%
Initial chromaticity	(3000K@, 0.4400, 0.40304000K@0.37600,36566500K@0.31300,3370) 6
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Driver failure rate at 5000 h	1.2 %
Median useful life L70B50	30,000 hour(s)

Product Data

Order product name	DN029B G2 LED10/CCT PSR-E D120 GM
Full product name	DN029B G2 LED10/CCT PSR-E D120 GM
Full product code	871951427358000
Order code	929002576508
Material Nr. (12NC)	929002576508
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514273580
Numerator - Packs per outer box	12
EAN/UPC - Case	8719514273597

SmartBright LED Downlight

